



LBKSystem

Volumetric Linear
Safety Barrier



Controller
LBK-C22

Smart sensor
LBK-S01

Mounting	Compatible with DIN rails	Fix bracket to machine or floor with XXmm diameter screws (screws not provided)
Enclosure material	-	PA66+GF
Colour	-	Light Blue
IP Grade	IP20	IP67
Operating Frequency	-	24GHz
Dimensions (W x H x D)	170 x 90 x 35 mm	147 x 125 x 53 mm
Weight	-	-
Price	R9 900.00 excl VAT	R11 900.00 excl VAT

LBKSystem Accessories

		Part. No.	Length	Net Price
	Sensor/controller cable DeviceNet/CANOpen, PVC, 5 poles, totally shielded	8047521	5 m	R380.64 excl VAT
	Sensor side: connector M12, female, A-coded, angled 90°	8047522	10 m	R584.14 excl VAT
	Controller side: free wires	-	-	-
	Sensor/sensor cable DeviceNet/CANOpen, PVC, 5 poles, totally shielded	8047536	5 m	R494.33 excl VAT
	IN side: connector M12, female, A-coded, angled 90° OUT side: connector M12, male, A-coded, angled 90°			
	Bus terminator M12, straight 180°, male, 5 poles, A-coded Between the poles 4 and 5, 1 resistance 120Ω ½W	07000003	-	R649.69 excl VAT

Prices based on ROE of R16.50 to 1 Euro